

Claims

1. A boiler convertible between a normal type and a condensing type, the boiler comprising:
a combustion chamber for generating high-temperature combustion heat by burning fuel therein;
a heat exchange section for applying heat to heating water by absorbing the high-temperature combustion heat; and
an outer housing formed at an inner portion thereof with a water reservoir for circulating the heating water, wherein coupling holes are formed in the outer housing, a circulation chamber is formed at a lower portion of the outer housing, a burner is provided at an upper portion of the combustion chamber so as to generate heat in a downward direction thereof, the combustion chamber is vertically installed in one of the coupling holes, a lower portion of the combustion chamber is communicated with the circulation chamber, the heat exchange section includes first and second heat exchangers and is vertically installed in the outer housing adjacent to the combustion chamber, an upper portion of the heat exchange section is coupled to one of the coupling holes and a lower portion of the heat exchange section is communicated with the circulation chamber, and a funnel is provided at an upper portion of the outer housing so as to discharge an exhaust gas derived from combustion of the fuel in the combustion chamber, and a noise-absorbing container is provided at the upper portion of the outer housing so as to connect the funnel with the outer housing.

2. The boiler as claimed in claim 1, wherein the outer housing is provided at an outer peripheral portion thereof with a hot water heat exchanger.

35

3. A boiler convertible between a normal type and a condensing type, the boiler comprising:

a combustion chamber for generating high-temperature combustion heat by burning fuel therein;

5 a heat exchange section including a main heat exchanger for absorbing sensible heat from the high-temperature combustion heat and a latent heat exchanger for absorbing remaining heat and latent heat from an exhaust gas outputted from the main heat exchanger, the
10 heat exchange section applying heat to heating water; and

an outer housing formed at an inner portion thereof with a water reservoir for circulating the heating water, wherein coupling holes are formed in the
15 outer housing, a circulation chamber is formed at a lower portion of the outer housing, the combustion chamber is vertically installed in one of the coupling holes, a burner is provided at an upper portion of the combustion chamber so as to generate heat in a downward
20 direction thereof, a lower portion of the combustion chamber is communicated with the circulation chamber, the main heat exchanger is vertically installed in the outer housing adjacent to the combustion chamber, the main heat exchanger is accommodated in one of the
25 coupling holes and a lower portion of the main heat exchanger is communicated with the circulation chamber, the latent heat exchanger is vertically installed in the outer housing adjacent to the main heat exchanger and is accommodated in one of the coupling holes, a lower
30 portion of the latent heat exchanger is shielded from the circulation chamber by means of a partition wall formed in the circulation chamber, a funnel is communicated with the latent heat exchanger through a funnel support so as to discharge an exhaust gas of the
35 latent heat exchanger to an exterior, and a noise

absorbing chamber is coupled to an upper portion of the outer housing so as to seal the upper portion of the outer housing while guiding the exhaust gas from the main heat exchanger to the latent heat exchanger.

5

4. The boiler as claimed in claim 3, wherein the partition wall is defined by an outer peripheral portion of the funnel support inserted into the circulation chamber from a lateral portion of the outer housing.

10

5. The boiler as claimed in claim 3, wherein the funnel support discharges condensing water generated from the latent heat exchanger and the funnel towards a neutralization unit.

15

6. The boiler as claimed in claim 3, wherein the outer housing is provided at an outer peripheral portion thereof with a hot water heat exchanger.

20

7. A method for converting a normal type oil boiler into a condensing type oil boiler or vice versa by using a convertible boiler as claimed in claim 1 or 2, the method comprising the steps of:

inserting a funnel support into a circulation chamber from a lateral portion of an outer housing of the boiler, thereby forming a partition wall for shielding the circulation chamber from a latent heat exchanger;

separating a funnel from a noise-absorbing container and sealing an upper portion of the noise-absorbing container; and

allowing the funnel to communicate with the latent heat through the funnel support in such a manner that a main heat exchanger absorbs sensible heat from an exhaust gas and the latent heat exchanger absorbs latent

heat from the exhaust gas while the exhaust gas is being circulated through a combustion chamber, the circulation chamber, the noise-absorbing container, the latent heat exchanger, the funnel support and the funnel.

5